



System Parts List:

- AT-200 - Transmitter
- AR-200 - Receiver
- ATR-400 - Repeater
- 103343 - 36" Coaxial Cable, SMA (M) to SMA (M)
(four per system)
- 909503-2 - DC Power & Audio Cable
(three per system)
- 103143 - Omni Antenna (four per system)

AT-200

Transmitter

- RF Power**
- STBY= RF off
 - Low = 0.25 Watts (+ 24 dBm)
 - High = 2.0 Watts (+ 33 dBm)



Channel Selector

Audio Selector

- 1L / 2L = Line level input (0 dBm - both audios)
- 1M / 2M = Mic Level Input (-50 dBm - both audios)
- 1M / 2L = Audio 1 is mic level, Audio 2 is line level
- 1L / 2M = Audio 1 is line level, audio 2 is mic level

RF Output



Power & Audio

Camera Input

AR-200

Receiver

- RSSI Measurement**
- 0 to 5 Vdc



Channel Selector

RF Antenna Input

Video Out

Rx Source Selector

- OFF
- TX - From Transmitter Only
- RPTR - From Repeater Only

Power & Audio

ATR-400

Repeater

- RSSI Measurement**
- 0 to 5 Vdc



Power & Audio

RF Rx Input

RF Tx Output

Video Out

Rx Source Selector

- OFF
- RPTR - Both Receiver and Transmitter Active
- RX - Receiver Only

Battery

BA-5390/U



Typical Battery Life for BA-5390/U

